

AMENDMENTS TO THE CLAIMS

A detailed listing of all claims that are, or were, in the present application, irrespective of whether the claim(s) remains under examination in the application are presented below. The claims are presented in ascending order and each includes one status identifier. Those claims not cancelled or withdrawn but amended by the current amendment utilize the following notations for amendment: 1. deleted matter is shown by strikethrough; and 2. added matter is shown by underlining.

1. (Currently Amended) A method for the simulation of spatial visual impressions, comprising the following steps:

a) ~~specification of~~ specifying the image generator geometry of an image generator, especially with regard to the structure and size of the image elements,

b) ~~specification of~~ specifying the filter array geometry of a filter array, especially with regard to the structure and size of the filter elements,

c) ~~specification of~~ specifying a spatial arrangement geometry in relation to the image generator and the filter array in a three-dimensional coordinate system (~~X, Y, Z~~),

d) ~~specification of~~ specifying a first and a second monocular position of observation in front of the said arrangement geometry in the said three-dimensional coordinate system (X, Y, Z),

e) ~~specification of~~ specifying a combined image that is suitable for display on the specified image generator geometry and that contains, in a defined assignment to the image

elements, image information from different given primary images, which are identical to different views  $A_k$  ( $k=1..n$ ) of a virtual or real scene or of a virtual or real object,

f) ~~determination of~~ determining a first and a second secondary image containing image elements of the specified combined image which are visible to the eye of an observer in the specified first and second monocular positions of observation on the basis of the specified filter array geometry in conjunction with the specified image generator geometry and the spatial arrangement geometry, in which an image element of a secondary image may explicitly just as well represent only part of an image element of the specified combined image, and

g) ~~stereoscopic visualization of~~ stereoscopically visualizing the first and second secondary images or parts of these secondary images as a left and right stereoscopic image, respectively.

2. (Currently Amended) A method as claimed in Claim 1, ~~characterized in that~~ wherein the views  $A_k$  from which the combined image gets its image information are views of a spatial test scene, which ~~preferably~~ contains two to five, ~~and even more preferably, three~~ ~~different graphic objects.~~

3. (Currently Amended) A method as claimed in Claim 2, wherein the test scene contains at least three graphic objects, ~~characterized in that~~ wherein the objects within the spatial test scene are arranged in different depth positions  $[[z \text{ each}]]$ , and wherein, if different views  $[[A_k]]$  are compared, ~~preferably exactly~~ one of the objects shows no horizontal displacement, ~~exactly~~ one shows a positive and ~~exactly~~ one shows a negative horizontal displacement.

4. (Currently Amended) A method as claimed in ~~any one of Claim[[s]] 2 or 3,~~  
~~characterized in that~~ wherein the objects imaged in the views  $[[A_k]]$  have a width of at least one  
full pixel column and a height of ~~preferably~~ at least about 24 pixel rows.

5. (Currently Amended) A method as claimed in ~~any one of Claim[[s]] 2 through 4,~~  
~~characterized in that~~ wherein the objects of the test scene are homogeneously black,  
homogeneously gray, or structured.

6. (Currently Amended) A method as claimed in ~~any one of Claim[[s]] 2 through 5,~~  
~~characterized in that~~ wherein the objects of the test scene are arranged in front of a white or  
structured background.

7. (Currently Amended) A method as claimed in ~~any one of Claim[[s]] 2 through 6,~~  
~~characterized in that~~ wherein the views  $[[A_k]]$  of the test scene are recorded with virtual or real  
cameras, wherein the axes of the virtual or real cameras are aligned in parallel or converging, and  
wherein ~~preferably~~ the camera positions used for every two neighboring views are always spaced  
at approximately equal distances.

8. (Currently Amended) A method as claimed in ~~any one of Claim[[s]] 2 through 6,~~  
~~characterized in that~~ wherein the views  $A_k$  for  $k > 1$  are generated ~~proceeding from~~ based on view  
 $A_1$ , in such a way that the view  $A_1$  is generated by ~~means of~~ a parallel projection of the test scene,

and ~~[[that]]~~, for generating the views  $A_k$  with  $k > 1$ , each of the graphic objects of the test scene imaged in view  $A_1$  are displaced horizontally, so that the measure of each displacement is proportional to the depth position of the respective object in the spatial test scene, and the measure of displacement selected for different views, ~~[[i.e.]]~~ represented by different vales of ~~[[K]]k~~, preferably varies.

9. (Currently Amended) A method as claimed in ~~any one of the above Claim~~~~[[s]]~~ 1, ~~characterized in that~~ wherein the image generator geometry ~~specified in step a)~~ is an orthogonal array of image elements in rows  $j$  and columns  $i$ , wherein the image elements emit or transmit light ~~of a specified wavelength or~~ of a specified wavelength range, and wherein each image element has an outline that can be described by a closed curve ~~and that is preferably polygonal or, even more preferably, rectangular.~~

10. (Currently Amended) A method as claimed in Claim 9, ~~characterized in that~~ wherein the image generator geometry is an orthogonal array of image elements in about 763 rows and about 3072 columns, wherein the first column emits or transmits essentially red light, the second column emits or transmits essentially green light, the third column emits or transmits essentially blue light, ~~the fourth column again emits or transmits essentially red light, etc., and~~ wherein a sequential pattern of essentially red, green and blue light emission or transmission repeats for remaining columns and wherein each image element has an essentially rectangular outline with a height of about 300  $[[\mu\text{m}]]$  micrometers and a width of about 100  $[[\mu\text{m}]]$  micrometers.

11. (Currently Amended) A method as claimed in ~~any one of the above Claim~~[[s]] 1, ~~characterized in that~~ wherein the filter array geometry of a filter array is specified ~~in step b)~~ in the form of a mask image, wherein wavelength filters, ~~[[and/or]]~~ gray level filters or a combination of the foregoing  $\beta_{pq}$ , [[i.e.]] that make up the filter elements of the filter array, are combined to form ~~[[such a]]~~ the mask image in an array of rows q and columns p depending on their transmission wavelength, ~~[[/]]~~ their transmission wavelength range ~~[[/]]~~ or their transmittance  $\lambda_b$ , according the following equation:

$$b = p - d_{pq} q - n_m \text{IntegerPart} \left[ \frac{p - d_{pq} q - 1}{n_m} \right], \text{ in which}$$

- p is the index of a wavelength or gray level filter  $\beta_{pq}$  in a row of the array
- q is the index of a wavelength or gray level filter  $\beta_{pq}$  in the position p,q, one of the intended transmission wavelengths or wavelength ranges, or a transmittance  $\lambda_b$ , respectively, and that can adopt values between 1 and  $b_{\max}$ ,
- $n_m$  is an integer great than zero,
- $d_{pq}$  is a selctable mask coefficient matrix for varying the generation of a mask image, and
- *IntegerPart* is a function for generating the larges integer that does not exceed the argument put in square brackets; and

in which each wavelength, ~~[[or]]~~ gray level filter or combination of the foregoing  $\beta_{pq}$  has an outline that can be described by a closed curve ~~and that is preferably polygonal or, even more preferably, rectangular,~~ and that ~~comprises~~ has a filter area of ~~a few 10,000  $\mu\text{m}^2$  up to several  $\text{mm}^2$~~  from about ten thousand square micrometers to about five square millimeters.

12. (Currently Amended) A method as claimed in Claim 11, ~~characterized in that~~ wherein each wavelength or gray level filter element is approximately one third as wide as an image element, and ~~[[that]]~~ wherein the mask image satisfies the parameters  $n_m=24$  and  $d_{pq}=1=\text{const}$ , wherein  $\lambda_1.. \lambda_{24}$  are transmission wavelength ranges ~~completely~~ substantially opaque to visible light.

13. (Currently Amended) A method as claimed in ~~any one of the above~~ Claim[[s]] 1, ~~characterized in that~~ wherein the spatial arrangement geometry specified in step c), relative to the image generator and the filter array in the said three-dimensional coordinate system  $[(X,Y,Z)]$ , ~~described~~ describes one plane each for the image generator and the filter array, and the spatial ~~position each~~ positions of ~~[[the]]~~ top left and bottom right corner points of the filter array or image generator.

14. (Currently Amended) A method as claimed in Claim 13, ~~characterized in that~~ wherein ~~[[the]]~~ a unit of measurement of the said coordinate system is ~~[[the]]~~ a millimeter, and in that the image generator plane satisfies the parameter

$z=0$  ~~[[mm]]~~ millimeters,

the filter array plane satisfies the condition

$z \in [-20... +20 \text{ mm}]$ ,

the position of the top left corner point of the filter array or of the image generator satisfies the parameters

$x = y = 0$  mm,

and the position of the bottom right corner point of the filter array or of the image generator satisfies the parameters

$x = 307.2$  mm and  $y = 230.4$  mm.

15. (Currently Amended) A method as claimed in ~~any one of the above~~ Claim[[s]] 1, ~~characterized in that~~ wherein the combined image to be specified in step e) is generated according to ~~the following rule~~ a process comprising the steps of:

- partitioning the views  $A_k$  ( $k=1 \dots n$ ) each into an equal grid of rows  $j$  and columns  $i$ ,
- combining the  $n$  views  $A_k$  in rows and columns to produce a single combined image with image elements  $\alpha_{ij}$ , with the assignment of bits of partial information from the views  $A_k$  ( $k=1 \dots n$ ) to image elements  $\alpha_{ij}$ , of the positions  $i,j$  being defined by the equation

$$k=i-c_{ij}j-n \text{ IntegerPart} \left[ \frac{i-c_{ij}j-1}{n} \right], \text{ in which}$$

- $i$  is the index of an image element  $\alpha_{ij}$ , in a row of the grid,
- $j$  is the index of an image element  $\alpha_{ij}$  in a column of the grid,
- $k$  is the consecutive number of the image  $A_k$  ( $k=1 \dots n$ ), from which the partial information originates that is to be rendered on a particular image element  $\alpha_{ij}$ ,
- $c_{ij}$  is a selectable coefficient matrix for combining or mixing on the grid the different bits of partial information originating from the images  $A_k$  ( $k=1 \dots n$ ), and

- *IntegerPart* is a function for generating the largest integer that does not exceed the argument put in square brackets.

16. (Currently Amended) A method as claimed in ~~any one of Claim[[s]] 1 through 14, characterized in that~~ wherein the combined image to be specified in step e) is generated according to ~~the following rule~~ a process comprising the steps of:

- portioning the views  $A_k$  ( $k=1\dots n$ ) each into an equal grid of rows  $j'$  and columns  $i'$ , by which a tensor  $A_{ki'j'}$  of order three is formed, which contains the bits of image information from views  $k$  ( $k=1\dots n$ ) in each equal grid  $(i'j')$ ,
- combining the bits of equal information  $A_{ki'j'}$ , to produce a single combined image with image elements  $\alpha_{ij}$  in grid  $(i,j)$ , with the assignment of bits of partial information from the tensor elements  $A_{ki'j'}$  ( $k=1\dots n$ ) to image elements  $\alpha_{ij}$  in the positions  $i,j$  of the grid  $(i,j)$  being defined by the equation

$$a_{ij} = \sum_k \sum_{i'} \sum_{j'} A_{ki'j'} g_{ki'j'ij} \text{ , in which}$$

- $(g)$  is a tensor of order five, the elements  $g_{ki'j'ij}$  of which are real numbers and have the effect of weighing factors that define the weight of the respective partial information  $(A_{ki'j'})$  in an image element  $\alpha_{ij}$ , and
- in which the grids  $(i,j)$  and  $(i',j')$  preferably have the same number of columns and the same number of rows.



17. (Currently Amended) A method as claimed in ~~any one of the above~~ Claim[[s]] 1, ~~characterized in that~~ wherein the determination of each of the secondary images according to step f) ~~is performed as follows~~ comprises the steps of:

- copying the combined image (with the image elements  $\alpha_{ij}$ ) to the respective secondary image to be produced,
- ~~determination~~ determining, for each individual image element copied in the secondary image, which area share of it is visible to the eye of an observer in the respective position of observation, allowance being made for the specified filter array geometry, the specified image generator geometry and the spatial arrangement geometry, and
- ~~modification (a) of~~ optionally, modifying the set value of each individual copied image element in the secondary image by multiplication of its original set value by the are quotient “determined visible area share of each individual copied image element in the secondary image, divided by the full area of the respective image element” and/or
- ~~modification (b) of~~ optionally, modifying the set value of each individual copied image element in the secondary image by multiplication of its original or already modified set value by a correction factor  $f_k$ , preferably  $0 \leq f_k \leq 1$ , and which is a measure of the wavelength and/or gray level filters lying between the observer’s eye in the respective position and the respective image element, or which is a measure of the wavelength-dependent or wavelength-independent transmittance

of all wavelength and/or gray level filters following the respective image element seen from the respective viewing direction.

18. (Currently Amended) A method as claimed in Claim 17, ~~characterized in that~~ wherein the optional steps of modifying modifications (a) and/or (b) of the set value of each individual copied image element in the secondary image, as described in detail for step f), make allowance for a function that is to be specified for a specified image generator, and that describes the functional relationship between the measurable luminance of an image element and its set value.

19. (Currently Amended) A method as claimed in ~~any one of Claim[[s]] 1 through 16, characterized in that~~ wherein the determination of each of the secondary images according to step f) is performed as follows comprises the steps of:

- Area scanning [[of]] the planar component lying closest to the respective monocular position of observation according to the specified arrangement geometry, [[i.e.]] of either [[a]] one of the filter arrays or the image generator, and, concurrently with the area scanning, ~~production of~~ producing a sufficiently resolved secondary image, which is an essentially correct replica of the respective visible area shares of the image elements of the combined image, or of the wavelength or gray level filters illuminated by these image elements, and making allowance ~~being made~~ for the specified filter array geometry—~~especially wavelength dependent or wavelength independent transmittances of the~~

~~wavelength or gray level filters~~, ~~the specified image generator geometry, and the spatial arrangement geometry.~~

20. (Currently Amended) A method as claimed in Claim 19, ~~characterized in that~~ wherein the determination of the secondary images described in detail for step f) makes allowance for a function that is to be specified for a specified image generator, and that describes the functional relationship between the measurable luminance of an image element and its set value.

21. (Currently Amended) A method as claimed in ~~any one of the above~~ Claim[[s]] 1, ~~characterized in that~~ wherein, in step g), provision is made for separate display of the secondary images to the left and the right eye, in which the secondary images are presented spatially side by side, spatially nested, or in temporal succession by ~~means of~~ an image generator, ~~or for example~~ a cathode ray tube, an LC display, a DMD projector or a plasma display, and in which the display of the secondary images is ~~particularly preferably~~ effected by ~~means of~~ an image generator that has the image generator geometry specified in step a), ~~especially with regard to the structure and size of the image elements.~~

22. (Currently Amended) A method as claimed in ~~any one of the above Claims,~~ ~~especially as claimed in Claim 21,~~ ~~characterized in that~~ wherein, in step g), an observer is caused to have a virtual [[3D]] three dimensional impression by ~~means of a stereoscopic visualization method~~ that visually fuses the secondary image pair or magnified sections of it.

23. (Currently Amended) A method as claimed in ~~any one of the above Claims,~~  
~~extended by a step h) that is performed after, or in parallel with, step g)~~ and that comprises the  
following operation Claim 1, further comprising the steps of:

- comparing spatially staggered and/or temporally staggered ~~comparison of the~~  
stereoscopically visualized first and second secondary images with a  
stereoscopically visualized image pair from the views  $A_k$ , in which preferably an  
image generator with approximately equal parameters each is used for the  
stereoscopic visualization of the first and second secondary images as well as for  
the stereoscopic visualization of the image pair from the views  $A_k$ , including the  
option that only sectional magnifications of the said images are visualized  
stereoscopically.

24. (Currently Amended) A method as claimed in ~~any one of the above Claim[[s]] 1,~~  
~~extended by a step i) that is performed after, or in parallel with, step g) or h), and that comprises~~  
~~the following operation:-~~ further comprising the steps of:

- ~~variation of~~ varying the first ~~[[and/]]~~ or second position of observation in at least  
one of their coordinates in the coordinate system (X,Y,Z), ~~and repeated execution~~  
~~of steps e) through g) or e) through h), and, optionally, any number of repetitions~~  
~~of the step i) described above.~~

25. (Currently Amended) An arrangement for implementing ~~[[the]]~~ a method of stimulating spatial visual impressions ~~as claimed in Claim 1~~, comprising:

- a) means for the digital specification of the image generator geometry of an age generator, ~~especially~~ with regard to the structure and size of the image elements,
- b) means for the digital specification of the filter array geometry of a filter array, ~~especially~~ with regard to the structure and size of the filter elements,
- c) means for the digital specification of a spatial arrangement geometry in relation to the image generator and the filter array in a three-dimensional coordinate system ~~(X,Y,Z)~~,
- d) means for the digital specification of a first and a second monocular position of observation in front of the said arrangement geometry in the said three-dimensional coordinate system ~~(X,Y,Z)~~,
- e) means for the specification of a combined image, which is suitable for display on the specified image generator geometry, and which, in a defined assignment to the image elements, contains bits of image information from different given primary images, which are identical to different views  ~~$A_k (k=1..n)$~~  of a virtual or real scene, or of a virtual or real object,
- f) means for the determination of a first and a second secondary image, which contains those image elements of the specified combined image that are visible to an observer's eye in the respective specified first and second monocular position of observation due to the specified filter array geometry in conjunction with the specified image generator and the spatial arrangement geometry, including the explicit option that one image element of a secondary image may represent only a part of an image element of the specified combined image, and

g) means for the stereoscopic visualization of the first and second secondary images or parts of these secondary images as a left and right stereoscopic image, respectively.

26. (Currently Amended) An arrangement as claimed in Claim 25, ~~characterized in that~~ wherein the means a) through f) are contained in a common unit configured as a software-controlled PC, and in that the means g) comprise a stereoscope, or shutter glasses and a monitor.

Please add new claims 27-31 as follows:

27. (New) A method as claimed in Claim 9, wherein each image element has a polygonal outline.

28. (New) A method as claimed in Claim 9, wherein each image element has a rectangular outline.

29. (New) A method as claimed in Claim 11, wherein each wavelength filter, graylevel filter has a polygonal outline.

30. (New) A method as claimed in Claim 11, wherein each wavelength filter, graylevel filter has a polygonal outline.

31. (New) A method as claimed in Claim 19, further comprising the step of making allowance for a factor selected from a group consisting of wavelength-dependent transmittance,

wavelength-independent transmittances of the wavelength or gray level filters, the specified image generator geometry, the spatial arrangement geometry and a combination of the foregoing.